

Maximum permitted weights and dimensions, goods transport Croatia

Height	4.00m
Width Motor vehicle / trailer Refrigerated vehicle or trailer (minimum thickness of walls: 50mm)	2.55m 2.60m
Length Motor vehicle Articulated vehicle Road train Car transporter	12.00m 16.50m 18.75m 21.00m
Weight per axle single axle single drive axle	10.00t 11.50t
 tandem axle of a motor vehicle, with a distance between the axles of less than 1.00m 1.00m to less than 1.30m 1.30m to less than 1.80m 1.30m to less than 1.80m, if the drive axle is fitted with twin tyres and 	11.00t 16.00t 18.00t
pneumatic suspension or equivalent tandem axle of a trailer or semi-trailer, with a distance between the axles of	19.00t
 less than 1.00m 1.00m to less than 1.30m 1.30m to less than 1.80m 1.80m or more 	11.00t 16.00t 18.00t 20.00t
tridem axle with a distance between two consecutive axles of up to 1.30m over 1.30m to 1.40m over 1.40m to 1.80m	21.00t 24.00t 27.00t
Maximum permitted weight Motor vehicle	
 with 2 axles with 3 axles with 3 axles 	18.00t 25.00t
 with 3 axles, if the drive axle is fitted with twin tyres and pneumatic suspension or equivalent with 4 axles 	26.00t 31.00t
 with 4 axles, if the drive axle is fitted with twin tyres and pneumatic suspension or equivalent Trailer 	32.00t
with 2 axleswith 3 axles	18.00t 24.00t
 Articulated vehicle with 4 axles (2+2) with 4 axles (2+2), if the distance between the axles of the semi-trailer is 	36.00t
over 1.80m and the drive axle is fitted with twin wheels and pneumatic suspension or equivalent with 5/6 axles with 5/6 axles (3+2/3) for the transport of 40' ISO container Road train	38.00t 40.00t 44.00t
with 4 axles (2+2) with 5/6 axles	36.00t 40.00t

Source: Transportkomerc, March 2015