

Maximum permitted weights and dimensions, goods transport Ireland

| Height ¹ | 4.25m |
|---|---------------------|
| Width | |
| Motor vehicle/trailer | 2.50m |
| Refrigerated vehicle (minimum thickness of walls 45mm) | 2.60m |
| Length | |
| Motor vehicle | 12.00m |
| Trailer | 12.00m |
| Articulated vehicle | 16.50m |
| Road train | 18.35m ² |
| Weight per axle | |
| single axle | 10.0t |
| drive axle, with a distance from the nearest axle of at least 1.20m | 10.5t |
| tandem axle of motor vehicle, with distance between the axles of | |
| · <1.00m | 11.5t |
| 1.00m to <1.30m | 16.0t |
| · 1.30m and over | 18.0t |
| 1.30m and over, and the drive axle is fitted with pneumatic suspension tandem axle of trailer or semi-trailer, with a distance between the axles of | 19.0t |
| · <1.00m | 11.0t |
| · 1.00m to <1.30m | 16.0t |
| · 1.30m to <1.80m | 18.0t |
| · 1.80m and over | 20.0t |
| tridem axle of trailer or semi-trailer, with a distance between the axles of | 20.00 |
| · 1.30m or less | 21.0t |
| · >1.30m to 1.40m | 22.5t |
| · >1.30m to 1.40m, and the drive axle is fitted with pneumatic suspension | 24.0t |
| Maximum permitted weight | |
| Motor vehicle | |
| · with 2 axles | 17.0t |
| · with 3 axles | 25.0t |
| · with 3 axles, and the drive axle is fitted with twin tyres and pneumatic | |
| suspension | 26.0t |
| · with 4 axles | 30.0t |
| with 4 axles, if the drive axle is fitted with twin tyres and pneumatic | |
| suspension, and the distance between the outermost axles is over 6.70m | 32.0t |
| Trailer | 40.01 |
| with 2 axles | 18.0t |
| · with 3 axles Articulated vehicle | 24.0t |
| · with 3 axles | 25 Ot |
| with 4 axles (2+2) | 25.0t 35.0t |
| with 5 axles (2+3) | 38.0t |
| with 5 axles (2+3) with pneumatic suspension | 40.0t |
| with 5/6 axles (3+2/3) | 40.0t |
| with 5/6 axles (3+2/3) for the transport of 40' ISO containers | 44.0t |
| Road train | |
| · with 4 axles (2+2) | 35.0t |
| with 5/6 axles (2+3, 3+2/3) | 40.0t |

¹ Drivers of vehicles which exceed a height of 3.65m must check their route as some bridges and tunnels have height restrictions

 $^2\,$ Provided the length of the consignment is 15.65m and the length of the cab 2.35m - otherwise, the maximum length remains 18.00m

Source: IRHA, November 1999