

## Maximum permitted weights and dimensions, goods transport Norway

| Height   | no restriction *                                   |
|--|--|
| Width Motor vehicle/trailer Refrigerated vehicle (minimum thickness of walls - 45mm)   | 2.55m<br>2.60m                                     |
| Length Motor vehicle Trailer Articulated vehicle Road train • with adjustable drawbar  | 12.0m<br>12.0m<br>17.50m<br>19.50m<br>19.50m       |
| Weight per axle on the main road network single axle drive axle tandem drive axle** tandem axle, with a distance between the axles of 1.20m - 1.29m 1.30m - 1.80m >1.80m                                   | 10.0t<br>11.5t<br>19.0t<br>16.0t<br>18.0t<br>20.0t |
| tridem axle, with a distance between the axles of 1.00m - 1.29m 1.30m - 1.80m  | 22.0t<br>24.0t                                     |
| Maximum permitted weight on the main road network  Motor vehicle   |  |
| <ul><li>with 2 axles</li><li>with 3 axles</li></ul>  | 19.0t<br>26.0t                                     |
| <ul> <li>with 4 axles, and the distance between the first and last axle</li> <li>exceeds 5.4m, and with two drive axles</li> <li>with 4 axles, and the distance between the first and last axle</li> </ul> | 30.0t  |
| exceeds 5.6m, and with two drive axles  with 4 axles, and the distance between the first and last axle  with 4 axles, and the distance between the first and last axle                                     | 31.0t  |
| exceeds 5.8m, and with two drive axles Trailer   | 32.0t  |
| <ul><li>with 2 axles</li><li>with 3 axles</li><li>with 4 axles</li><li>Semi trailer</li></ul>  | 20.0t<br>28.0t<br>30.0t                            |
| <ul> <li>with 2 axles</li> <li>with 2 axles, if distance between the first axle and last steering axle exceeds 1.79m**</li> </ul>  | 18.0t<br>20.0t                                     |
| <ul> <li>with 3 axles</li> <li>with 3 axles, if distance between the first axle and last steering axle exceeds 1.79m**</li> </ul>  | 24.0t<br>27.0t                                     |
| Road train with 6 axles**  | 50.0t  |
| Modular- and timber- road train with 7 axles**   | 60t  |

<sup>\*</sup> however, there are many low bridges and tunnels – see detailed map obtainable from the Vegdirektoratet

Source: NLF, April 2015

<sup>\*\*</sup> more detailed rules apply